

Ambient Air Quality Monitoring (AAQM) Report October 2022

West Gate Tunnel Project

Submitted to:

Mr Tim Spawton

CPB JH Joint Venture West Gate Tunnel Project Level 11, 5 Bowen Crescent Melbourne VIC 3004

Submitted by:

Golder

Building 7, Botanicca Corporate Park 570 – 588 Swan Street Richmond, Victoria 3121 Australia

+61 3 8862 3500

1789878-051-R-Rev0

Issued: December 2022



Accreditation No. 1910

Accredited for compliance with ISO/IEC 17025 - Testing.

Record of Issue

Company	Client Contact	Version	Date Issued	Method of Delivery	Amendment
CPB JH WGT Project	Tim Spawton	Rev A	22/11/2022	Electronic	Draft
CPB JH WGT Project	Tim Spawton	Rev 0	15/12/2022	Electronic	Original

Distribution List

1 electronic copy - CPB JH Joint Venture

1 electronic copy - Golder Associates Pty Ltd



Executive Summary

Air quality monitoring for the West Gate Tunnel Project has been specifically established to develop a "baseline" of data from current local conditions. This baseline will be used to measure any changes once the tunnel opens. When the project opens, air quality monitoring will continue for up to 5 years.

The results of the West Gate Tunnel Project Ambient Air Quality Monitoring (AAQM) program for the period of 1 October 2022 to 31 October 2022 are presented below.

The following tables present the maximum measured concentration for each parameter at Stations 1, 2, 3, 4, 5 and 6 during the reporting period. The maximum concentration for each parameter is compared with the respective criteria.

Station	1	Summary	October	2022
---------	---	---------	---------	------

Parameter	Units	Averaging period	Maximum concentration	Air quality objective ^A	Exceedances ^B
PM _{2.5}	ug/m ³	24 hour	12	25	Nil
PM ₁₀	ug/m ³	24 hour	30	50	Nil

Note:

A – SEPP(AAQ) objective

B - Exceedances refers to the number of individual days the criterion was exceeded at any station

Station 2, Station 3, Station 5 and Station 6 Summary October 2022

Deremeter	Unito	Averaging	Maximum concentration				Air quality	ExceedencesB
Parameter Uni	Units	period	Station 2	Station 3	Station 5	Station 6	objective ^A	Exceedances
PM _{2.5}	ug/m ³	24 hour	12	11	10	12	36	Nil
PM ₁₀	ug/m ³	24 hour	29	22	27	43	60	Nil

Note:

A - SEPP(AQM) Intervention level

B - Exceedances refers to the number of individual days the criterion was exceeded at any station

Station 4 Summary October 2022

Parameter	Units	Averaging period	Maximum concentration	Air quality objective	Exceedances ^c
PM _{2.5}	ug/m ³	24 hour	13	36 ^A	Nil
PM10	ug/m ³	24 hour	45	60 ^A	Nil
NO ₂	ppb	1 hour	60	140 ^A	Nil
СО	ppm	1 hour	2.2	29 ^A	Nil
Benzene	ppb	24 hour	<0.5	3.0 ^B	Nil
Toluene	ppb	24 hour	1.1	1000 ^B	Nil
Total xylene isomers	ppb	24 hour	<1	250 ^B	Nil

Note:

A - SEPP(AQM) Intervention level

B - Air NEPM Monitoring investigation level

C - Exceedances refers to the number of individual days the criterion was exceeded at any station



October 2022 ambient air quality monitoring programme results were less than the respective air quality objectives for all parameters measured at all ambient air quality stations.

Data capture statistics for October 2022 were above 90 percent for all parameters at all stations.

A construction area (Millers Road exit ramp and noise wall relocation) is now adjacent Station 4, as a result, the measured pollutant concentrations may not be representative of traffic emissions.



Table of Contents

1.0	INTRO	DUCTION	1
2.0	AAQM	S DETAILS	2
	2.1	Site locations	2
	2.2	Siting assessment	3
	2.3	Equipment specifications	4
3.0	AIR QI	JALITY CRITERIA	4
	SEPP	(AAQ)	5
	SEPP(AQM)	5
	NEPM	(Air Toxics)	5
4.0	TEST I	METHODS	6
	4.1	Particulate matter (PM _{2.5})	6
	4.2	Particulate matter (PM ₁₀)	6
	4.3	Nitrogen dioxide (NO ₂)	7
	4.4	Carbon monoxide (CO)	7
	4.5	Volatile organic compounds (BTEX)	7
	4.6	Meteorological parameters	7
5.0	MEAS	UREMENT UNCERTAINTY	7
	5.1	PM _{2.5}	7
	5.2	PM ₁₀	7
	5.3	NO ₂	8
	5.4	CO	8
	5.5	Benzene	8
	5.6	Meteorological parameters	8
	5.7	Calibration and maintenance	8
6.0	RESUI	_TS	9
	6.1	Particulate matter (BAM PM _{2.5} & PM ₁₀)	9
	6.1.1	Station 1 – Yarraville Gardens 1	0
	6.1.2	Station 2 – Francis Street 1	1
	6.1.3	Station 3 – Railway Reserve 1	2

9.0	IMPOF	RTANT INFORMATION RELATING TO THIS REPORT	27
8.0	DISCU	ISSION	26
	7.2	Data validation	26
	7.1	Data capture2	25
7.0	QUAL	ITY ASSURANCE	25
	6.5.9	Wind rose – Station 5 (Donald McLean Reserve)2	<u>2</u> 4
	6.5.8	Wind rose – Station 4 (Primula Avenue)2	24
	6.5.7	Wind rose – Station 3 (Railway Reserve)2	23
	6.5.6	Wind rose – Station 2 (Francis Street)2	23
	6.5.5	Wind rose – Station 1 (Yarraville Gardens)	22
	6.5.4	Wind speed	22
	6.5.3	Atmospheric pressure	21
	6.5.2	Relative humidity	20
	6.5.1	Ambient temperature	20
	6.5	Meteorological parameters	20
	6.4	Volatile organic compounds (BTEX)	19
	6.3	Carbon monoxide (CO)	18
	6.2	Nitrogen dioxide (NO ₂)	17
	6.1.7	Combined PM _{2.5} mass concentrations	16
	6.1.6	Station 6 – Millers Road	15
	6.1.5	Station 5 – Donald McLean Reserve	14
	6.1.4	Station 4 – Primula Avenue	13

TABLES

Station 1 Summary October 2022	ii
Station 2, Station 3, Station 5 and Station 6 Summary October 2022	ii
Station 4 Summary October 2022	ii
Table 1: AAQMS monitoring details	. 1
Table 2: AAQMS commissioning dates	. 2
Table 3: Australian standard AAQMS siting criteria compliance	. 3
Table 4: AAQMS instrumentation	. 4
Table 5: Air quality indicators and objectives	. 5
Table 6: Meteorological parameters measurement uncertainty	. 8

Table 7: Calibrations	8
Table 8: Station 1 (Yarraville Gardens AAQMS) PM _{2.5} and PM ₁₀ percentiles (24 hour average)	10
Table 9: Station 2 (Francis Street AAQMS) $PM_{2.5}$ and PM_{10} percentiles (24 hour average)	11
Table 10: Station 3 (Railway Reserve AAQMS) PM _{2.5} and PM ₁₀ percentiles (24 hour average)	12
Table 11: Station 4 (Primula Avenue AAQMS) $PM_{2.5}$ and PM_{10} percentiles (24 hour average)	13
Table 12: Station 5 (Donald McLean Reserve AAQMS) $PM_{2.5}$ and PM_{10} percentiles (24 hour average	e)14
Table 13: Station 6 (Millers Road AAQMS) PM _{2.5} and PM ₁₀ percentiles (24 hour average)	15
Table 14: Station 4 (Primula Avenue AAQMS) NO ₂ percentiles (1 hour average)	17
Table 15: Station 4 (Primula Avenue AAQMS) CO percentiles (1 hour average)	18
Table 16: Station 4 - Primula Avenue AAQMS BTEX concentrations (24 hour average)	19
Table 17: Data Capture	25
Table 18: Station 1 Summary – October 2022	26
Table 19: Station 2, Station 3, Station 5 and Station 6 Summary – October 2022	26
Table 20: Station 4 Summary – October 2022	27

FIGURES

Figure 1: West Gate Tunnel AAQMS site locations	3
Figure 2: Station 1 PM _{2.5} and PM ₁₀ concentration (24 hour average) – October 2022	10
Figure 3: Station 2 PM _{2.5} and PM ₁₀ concentration (24 Hour Average) – October 2022	11
Figure 4: Station 3 $PM_{2.5}$ and PM_{10} concentration (24 hour average) – October 2022	12
Figure 5: Station 4 $PM_{2.5}$ and PM_{10} concentration (24 hour average) – October 2022	13
Figure 6: Station 5 $PM_{2.5}$ and PM_{10} concentration (24 hour average) – October 2022	14
Figure 7: Station 6 $PM_{2.5}$ and PM_{10} concentration (24 hour average) – October 2022	15
Figure 8: Combined PM _{2.5} concentration (24 hour average) – October 2022	16
Figure 9: Combined PM ₁₀ concentration (24 hour average) – October 2022	16
Figure 10: Station 4 NO ₂ concentration (1 hour average) – October 2022	17
Figure 11: Station 4 CO concentration (1 hour average) – October 2022	18
Figure 12: Ambient temperature (1 hour average) All AAQMS – October 2022	20
Figure 13: Relative humidity (1 hour average) All AAQMs – October 2022	21
Figure 14: Atmospheric pressure (1 hour average) Station 4 Primula Avenue – October 2022	21
Figure 15: Wind speed (1 hour average) All AAQMs – October 2022	22
Figure 16: Wind speed (1 hour average) Station 1 - Yarraville Gardens	22
Figure 17: Wind speed (1 hour average) Station 2 - Francis Street	23
Figure 18: Wind speed (1 hour average) Station 3 - Railway Reserve	23
Figure 19: Wind speed (1 hour average) Station 4 - Primula Avenue	24



APPENDICES

APPENDIX A Data Exceptions

APPENDIX B Laboratory Certificates

APPENDIX C Important Information Relating to this Report



1.0 INTRODUCTION

Air quality monitoring for the West Gate Tunnel Project has been specifically established to develop a "baseline" of data from current local conditions. This baseline will be used to measure any changes once the tunnel opens. When the project opens, air quality monitoring will continue for up to 5 years.

The results of the West Gate Tunnel Project Ambient Air Quality Monitoring (AAQM) program for the period of 1 October 2022 to October 31, 2022, are contained in the following report.

The AAQM program was conducted in accordance with the Environmental Performance Requirement (EPR) AQP4 for the Project and consists of six AAQM stations (AAQMS) monitoring the following ambient air quality indicators:

- continuous measurement of particulate matter with an equivalent aerodynamic diameter less than 10 microns (PM₁₀)
- continuous measurement of particulate matter with an equivalent aerodynamic diameter less than 2.5 microns (PM_{2.5})
- continuous measurement of wind speed and wind direction.

Additionally, one of the specified AAQMS (Primula Avenue) monitors the following additional air quality indicators in combination with PM_{10} and $PM_{2.5}$:

- continuous monitoring of oxides of nitrogen ([NO_x] comprising of nitrogen dioxide (NO₂) and nitric oxide [NO])
- continuous monitoring of carbon monoxide (CO)
- one in six day monitoring of benzene, toluene, ethylbenzene and xylene isomers (BTEX)
- continuous measurement of atmospheric pressure.

AAQMS Station 1 to Station 6 were installed and commissioned during the period 22/08/2018 to 12/10/2018. Specific installation dates can be found below in Section 2.1.

Details of the air quality indicators monitored at each AAQMS are provided in Table 1.

Site name	Location	Coordinates	Monitoring parameters
Station 1	Barbara Beyer Reserve, 2 Harris Street, Yarraville	-37.812730°S 144.900017°E	PM ₁₀ and PM _{2.5} Ambient temperature, relative humidity, wind speed and wind direction
Station 2	51-53 Francis Street	-37.821800°S 144.894383°E	PM ₁₀ and PM _{2.5} Ambient temperature, relative humidity, wind speed and wind direction
Station 3	Railway Lot 64, (part) 15 Goulburn Street, Yarraville	-37.814063°S 144.891320°E	PM ₁₀ and PM _{2.5} Ambient temperature, relative humidity, wind speed and wind direction
Station 4	44 Primula Avenue, Brooklyn	-37.824284°S 144.846425°E	PM ₁₀ and PM _{2.5} NO, NO ₂ , NOx and CO BTEX – one in six day sampling (24 hour average)

Table 1: AAQMS monitoring details



Site name	Location	Coordinates	Monitoring parameters
			Ambient temperature, relative humidity, atmospheric pressure, wind speed and wind direction
Station 5	Donald McLean Reserve, Spotswood	-37.826442°S 144.882133°E	PM ₁₀ and PM _{2.5} Ambient temperature, relative humidity, atmospheric pressure, wind speed and wind direction
Station 6	44 Millers Road Brooklyn	-37.821252°S 144.848878°E	PM ₁₀ and PM _{2.5} Ambient temperature and relative humidity

AAQMS DETAILS 2.0

2.1 **Site locations**

AAQMS Station 1 to Station 5 were installed and commissioned during the period 22/08/2018 to 31/08/2018. AAQMS Station 6 (Millers Road) was commissioned on 12/10/2018. Meteorological sensors (wind speed and direction) were installed later due to delays in calibration from the instrument supplier. AAQMS commissioning dates are provided in Table 2. Figure 1 presents the locations of the AAQMS.

Table 2: AAQ	MS commiss	ioning dates
--------------	------------	--------------

Parameter	Station 1	Station 2	Station 3	Station 4	Station 5	Station 6
AAQMS	23/08/2018	22/08/2018	22/08/2018	22/08/2018	31/08/2018	12/10/2018
Wind speed & direction	07/09/2018	20/09/2018	14/09/2018	10/09/2018	17/09/2018	23/11/2018 ^A

A - wind sensor is not compliant with siting criteria specified in AS 3580.14





Figure 1: West Gate Tunnel AAQMS site locations

2.2 Siting assessment

Australian Standard AS/NZS 3580.1.1 "Methods for Sampling and Analysis of Ambient Air – Part 1.1. Guide to Siting Air Monitoring Equipment" provides general guidance for the siting of ambient air monitoring equipment and specific siting parameters for individual air pollutants. Table 3 provides a comparison between recommended criteria contained in the Standard for the parameters monitored at neighbourhood and peak monitoring stations with actual conditions at each AAQMS.

Station	Station 1	Station 2	Station 3	Station 4	Station 5	Station 6
Station type	Neighbourhood	Peak	Peak	Peak	Peak	Peak
Inlet height above ground level 1.0 m – 15 m	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Clear sky angle 120° (Neighbourhood)		-	-	-	-	-
Unrestricted 270° airflow around inlet (Neighbourhood)		-	-	-	-	-
Unrestricted 180° airflow around inlet (Peak)	-	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Distance to supporting structure ≥ 1 m	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark

Table 3: Australian standard AAQMS siting criteria compliance



Station	Station 1	Station 2	Station 3	Station 4	Station 5	Station 6
Station type	Neighbourhood	Peak	Peak	Peak	Peak	Peak
10 m from drip line of trees	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	×A
No extraneous sources nearby	\checkmark	\checkmark	\checkmark	×B	\checkmark	×C
Greater than 50 m from road (≤ 10,000 vehicles/day)	\checkmark	-	-	-	-	-
Greater than 2 m from road (Peak station)	-	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark

Note:

A Tree drip line is <3 m from sampler inlets and meteorological monitoring equipment

B Temporary construction area for Millers Road noise wall and exit ramp relocation works

C Residential chimney is <5 m from the sampler inlet.

2.3 Equipment specifications

Table 4 provides a list of the monitoring equipment installed at the AAQMS.

Table	4:	AAQMS	instrumentation
IUNIO	- T •	AAGINO	monunom

Parameter	Equipment item	Manufacturer	Model
PM _{2.5}	Beta Attenuation Monitor (BAM)	Thermo Fisher Scientific Inc.	5014i
PM10	Beta Attenuation Monitor (BAM)	Thermo Fisher Scientific Inc.	5014i
Oxides of Nitrogen	Chemiluminescence	Thermo Fisher Scientific Inc.	42i
Carbon Monoxide	Infra-red gas filter correlation	Thermo Fisher Scientific Inc.	48i
Temperature	Pt100 resistive platinum sensor	Thermo Fisher Scientific Inc.	5014i
BTEX	Summa canister	Restek	6 litre
Relative humidity	Capacitive thin film sensor	Thermo Fisher Scientific Inc.	5014i
Atmospheric Pressure	Beta Attenuation Monitor (BAM)	Thermo Fisher Scientific Inc.	5014i
Wind speed and wind direction	Ultrasonic anemometer	RM Young	Model 86000

3.0 AIR QUALITY CRITERIA

The ambient air quality criteria applicable to the West Gate Tunnel Project were derived from the State Environment Protection Policies (SEPPs); Ambient Air Quality (SEPP(AAQ)), Air Quality Management (SEPP(AQM)) and the National Environment Protection (Air Toxics) Measure Monitoring Investigation Levels (MILs).

As part of the implementation of the Environment Protection Act 2017 (Act) which came into effect on 1 July 2021, the SEPP(AAQ) and SEPP(AQM) have been discontinued and some of their content has been replaced

by the "Environment Reference Standard" (ERS), publication S245. In addition, some elements of the SEPP's will ultimately be replaced by proposed guidelines.

EPA publication 1998 - June 2021 "Compliance Code for Victoria's Big Build Projects" states for the West Gate Tunnel Project, the obligations under Section 25(1) of the Act for General Environmental Duty (GED) are met during design and construction by complying with the West Gate Tunnel Project Environmental Performance Requirements (EPRs), which include undertaking ambient air quality monitoring in accordance with SEPP(AAQ) and SEPP(AQM). This report therefore continues to make reference to the SEPP(AAQ) and SEPP(AQM).

SEPP (AAQ)

The SEPP(AAQ) sets out the environmental indicators and objectives for ambient air quality that seek to achieve or maintain environmental values in Victoria. The SEPP(AAQ) adopts the requirements of the National Environment Protection (Ambient Air Quality) Measure (Air NEPM) and its environmental quality objectives (EQOs) for CO, NO₂, and particles (as PM₁₀ and PM_{2.5}). The SEPP(AAQ) EQOs apply to air quality within a region or sub-region considered to be representative of exposure of the general population in Victoria. These objectives have been adopted for the purposes of comparison with results from background/ neighbourhood monitoring stations for the West Gate Tunnel Project and are relevant to Station 1 (Yarraville Gardens).

SEPP(AQM)

The SEPP(AQM) sets out legislative requirements for managing and assessing air emissions in Victoria. The aim of the SEPP(AQM) is to ensure that prescribed air quality objectives are met and protect the beneficial uses of the air environment. Schedule B lists intervention levels which are used in the assessment of local or neighbourhood air monitoring data. Consistent with assessment of impacts described in the Environment Effects Statement for the West Gate Tunnel Project, the SEPP(AQM) intervention levels will continue to be adopted for purposes of comparison with results from peak monitoring stations for the West Gate Tunnel Project. These AQO are applicable to Station 2 (Francis Street), Station 3 (Railway Reserve), Station 4 (Primula Avenue), Station 5 (Donald McLean Reserve) and Station 6 (Millers Road).

NEPM (Air Toxics)

The aim of the Air Toxics NEPM is to gain a greater understanding of the levels of air toxics at specific locations where elevated concentrations are likely to occur and where the potential for significant human exposure exists. The Air Toxics NEPM established monitoring investigation levels (MILs) relevant for the West Gate Tunnel Project for benzene, toluene and xylene isomers. The MILs are used purposes of comparison with results from the air toxics monitored at Station 4 (Primula Avenue). Table 5 presents the air quality indicators and objectives for each AAQMS for the West Gate Tunnel Project.

Location	Pollutant	Units	Air Quality Objective	Averaging period
			50	24 hour
Station 1	FIVI10	µg/m³	20	Annual
	PM _{2.5}		25	24 hour
			8	Annual

Table 5: A	١r	quality	indicators	and	objectives
------------	----	---------	------------	-----	------------



Location	Pollutant	Units	Air Quality Objective	Averaging period
Station 2 Station 3	PM ₁₀		60	
Station 4 Station 5 Station 6	PM _{2.5}	µg/m³	36	24 nour
	CO	ppm	29	1 hour
	NO ₂	ppb	140	1 hour
	Benzene	ppb	3	Annual
Station 4	Taluana	anh	1000	24 hour
Station 4	Toluene	рро	100	Annual
	Ethylbenzene	Ethylbenzene ppb		24 hour
	Vulana inemata	and	250	24 hour
	Aylene Isomers	αqq	200	Annual

4.0 TEST METHODS

4.1 Particulate matter (PM_{2.5})

PM_{2.5} concentrations are determined using a Beta Attenuation Monitor (BAM).

Suspended particulate matter in ambient air is measured using the attenuation of beta rays as a surrogate for continuous mass determination. Beta rays are high energy electrons generated from the radioactive decay of the radon isotope Rn-222. When contacting particulate matter beta rays are either absorbed or their energy level is diminished. The relationship between the attenuation of beta rays between the source and detector is used to determine the mass density.

The BAM is equipped with a flow control and measurement system. The flow control system volumetrically controls the flowrate to 16.7 l/min. The flowrate is used with the mass density to calculate the particulate matter concentration.

The sampler is fitted with a size selective inlet, which separates particles with an equivalent aerodynamic diameter greater than 10 microns from the sample stream. An in-line $PM_{2.5}$ particle size separator is also fitted to further separate particles; only those with an equivalent aerodynamic diameter less than 2.5 microns can pass through the particle size separator to the filter for mass determination.

The PM_{2.5} monitoring method is based on the requirements contained within Australian Standard AS/NZS 3580.9.12 "*Methods for Sampling and Analysis of Ambient Air – Method 9.12: Determination of Suspended Particulate Matter – PM*_{2.5} Beta Attenuation Monitors" (NATA Laboratory Accreditation No. 1910).

4.2 Particulate matter (PM₁₀)

 PM_{10} concentrations are determined using a continuous BAM without an in-line $PM_{2.5}$ particle size separator. All other measurement processes remain the same as for the $PM_{2.5}$ test method. The PM₁₀ monitoring method is based on the requirements contained within Australian Standard AS/NZS 3580.9.11:2016 "*Methods for Sampling and Analysis of Ambient Air – Method 9.11: Determination of Suspended Particulate Matter – PM₁₀ Beta Attenuation Monitors" (NATA Laboratory Accreditation No. 1910).*

4.3 Nitrogen dioxide (NO₂)

Oxides of nitrogen concentrations were determined using a 42i Thermo Scientific chemiluminescence gas analyser.

Automatic calibrations are carried out daily against a NATA certified reference gas mixture. Manual calibrations are conducted at one month intervals.

The oxides of nitrogen (NO, NO₂ and NO_x) monitoring method is based on the requirements of Australian Standard AS 3580.5.1, *"Determination of Oxides of Nitrogen – Chemiluminescence Method"*.

4.4 Carbon monoxide (CO)

Carbon monoxide concentrations are determined using a 48i Thermo Scientific infra-red gas filter correlation analyser.

Automatic calibrations are carried out daily against a NATA certified reference gas mixture. Manual calibrations are conducted at one month intervals.

The carbon monoxide monitoring method is based on the requirements of Australian Standard AS 3580.7.1, "Determination of Carbon Monoxide – Direct Reading Instrumental Method".

4.5 Volatile organic compounds (BTEX)

A sample is collected in an evacuated electro-polished and passivated stainless steel canister. Analysis involves separation by gas chromatography (GC) and measurement by mass selective (MS) detector.

The procedure for sampling Volatile Organic Compounds (VOCs) using evacuated canisters, and for the subsequent analysis, is described in USEPA Method TO-15 "Determination of Volatile Organic Compounds (VOCs) in air collected in specially-prepared canisters and analysed by Gas Chromatography/Mass Spectrometry (GC/MS)".

Samples were analysed by Queensland Health (NATA Laboratory Accreditation No. 41) based on USEPA method TO-15. The test method used was in accordance with Golder Source Test Method C9, "Canister (Evacuated) Sampling for VOC: In Ambient Air and Source Emissions".

4.6 Meteorological parameters

Monitoring of meteorological parameters; wind speed/direction, temperature, relative humidity, solar radiation and rainfall was conducted in accordance with Australian Standard AS 3580.14 "*Methods for Sampling and Analysis of Ambient Air – Part 14: Meteorological Monitoring for Ambient Air Quality Monitoring Applications*" (NATA Laboratory Accreditation No. 1910).

5.0 MEASUREMENT UNCERTAINTY

5.1 PM_{2.5}

The measurement uncertainty for PM_{2.5} by BAM is published by Thermo-Fisher as ±2 µg/m³ (24 hour average).

5.2 **PM**₁₀

The measurement uncertainty for PM_{2.5} by BAM is published by Thermo-Fisher as ±2 µg/m³ (24 hour average).



5.3 NO₂

The measurement uncertainty for NO, NO2 and NOx by Chemiluminescence is published in AS3580.5.1 as ±10% (24 hour average).

5.4 CO

The measurement uncertainty for CO by Infra-red gas filter correlation is published in AS3580.7.1 as ±10% (24 hour average).

5.5 Benzene

USEPA Method TO-15 cites the accuracy and precision for two ambient air quality studies conducted in the United States of America. The average replicate precision for a range of 16 compounds in both studies was 15%. Replicate precision was defined as the ratio of the average difference between replicates to the average value of replicates.

The reported accuracies for both studies ranged between ± 4 % and ± 31 %. The average accuracy for both studies for the range of 16 compounds was ± 11%. Accuracy is defined as the ratio of the difference between expected and observed audit results to the expected audit result.

5.6 Meteorological parameters

The estimated measurement uncertainty for each of the parameters is presented in Table 6.

Parameter	Measurement uncertainty ^A
Wind speed	Greater of ±0.6 m/s or 5%
Wind direction	±5°
Barometric pressure	±3 hPa
Temperature	±6%
Relative humidity	±5 – 7%RH

Table 6: Meteorological parameters measurement uncertainty

Note:

Measurement uncertainty estimates are as published in AS3580.14 "Methods for Sampling and Analysis of Ambient Air - Part 14 А Meteorological Monitoring for Ambient Air Quality Monitoring Applications".

5.7 Calibration and maintenance

Sample flow rate calibration was conducted on a monthly basis using a NATA calibrated primary standard flowmeter. Calibration details for the reporting period are presented in Table 7.

Location	Parameter	Last Calibration Date	Calibration Type	
	PM ₁₀	28/09/2022	Monthly	
Station 1	PM _{2.5}	28/09/2022	Monthly	
	Wind speed and direction	25/08/2022	Two yearly	
	PM ₁₀	28/09/2022	Monthly	
Station 2	PM _{2.5}	28/09/2022	Monthly	



Location	Parameter	Last Calibration Date	Calibration Type
	Wind speed and direction	20/08/2022	Two yearly
	PM ₁₀	28/09/2022	Monthly
Station 3	PM _{2.5}	28/09/2022	Monthly
	Wind speed and direction	12/10/2022	Two yearly
	PM ₁₀	26/09/2022	Monthly
	PM _{2.5}	26/09/2022	Monthly
	NO/ NO2 / NOx	21/09/2022	Monthly
Station 4	СО	21/09/2022	Monthly
	BTEX	NA	Flow-controllers and canisters certified by lab
	Wind speed and direction	11/09/2022	Two yearly
	PM ₁₀	30/09/2022	Monthly
Station 5	PM _{2.5}	30/09/2022	Monthly
	Wind speed and direction	10/10/2022	Two yearly
	PM ₁₀	30/09/2022	Monthly
Station 6	PM _{2.5}	30/09/2022	Monthly

6.0 RESULTS

The monitoring results for 1 October 2022 to 31 October 2022 are presented in the following sections.

6.1 Particulate matter (BAM PM_{2.5} & PM₁₀)

PM_{2.5} and PM₁₀ were continuously monitored and 5-minute averages logged. The 5-minute average data was transformed to 24 hour averages for reporting.

PM_{2.5} and PM₁₀ concentration statistics from the reporting period for Station 1 to Station 6 are presented in Table 8 to Table 13. The 24 hour average plots for Station 1 to Station 6 are presented in Figure 2 to Figure 7.



6.1.1 **Station 1 – Yarraville Gardens**

Table 8: Station 1 (Yarraville Gardens AAQMS) PM2.5 and PM10 percentiles (24 hour average)

Parameter		Air quality objective ^B						
	Maximum	99 th	98 th	95 th	90 th	75 th	50th	(µg/m³)
PM _{2.5}	12	12	11	10	8.9	7.7	4.6	25
PM ₁₀	30	28	27	24	24	19	12	50

Note:

A Micrograms per cubic metre at 0°C and 101.3 kPa B SEPP(AAQ) Objective Values rounded to two significant figures.



Figure 2: Station 1 PM_{2.5} and PM₁₀ concentration (24 hour average) – October 2022



6.1.2 **Station 2 – Francis Street**

Table 9: Station 2 (Francis Street AAQMS) PM2.5 and PM10 percentiles (24 hour average)

Parameter		Air quality objective ^B						
	Maximum	99 th	98 th	95 th	90 th	75 th	50th	(µg/m³)
PM _{2.5}	12	12	11	9.8	8.9	7.0	4.4	36
PM10	29	28	27	26	24	16	13	60

Note:

A Micrograms per cubic metre at 0°C and 101.3 kPa B SEPP(AQM) Intervention level Values rounded to two significant figures.



Figure 3: Station 2 PM_{2.5} and PM₁₀ concentration (24 Hour Average) – October 2022



6.1.3 Station 3 – Railway Reserve

Table 10: Station 3 (Railway Reserve AAQMS) PM2.5 and PM10 percentiles (24 hour average)

Parameter		Air quality objective ^B						
	Maximum	99 th	98 th	95 th	90 th	75 th	50th	(µg/m³)
PM _{2.5}	11	11	10	9.4	8.1	6.6	4.5	36
PM ₁₀	22	21	21	20	18	15	9.3	60

Note:

A Micrograms per cubic metre at 0°C and 101.3 kPa B SEPP(AQM) Intervention level Values rounded to two significant figures.



Figure 4: Station 3 PM_{2.5} and PM₁₀ concentration (24 hour average) – October 2022



6.1.4 Station 4 – Primula Avenue

Table 11: Station 4 (Primula Avenue AAQMS) PM2.5 and PM10 percentiles (24 hour average)

Parameter		Air quality objective ^B						
	Maximum	99 th	98 th	95 th	90 th	75 th	50th	(µg/m³)
PM _{2.5}	13	13	13	12	10	7.4	4.4	36
PM10	45	44	44	39	34	23	12	60

Note:

A Micrograms per cubic metre at 0°C and 101.3 kPa B SEPP(AQM) Intervention level Values are rounded to two significant figures.



Figure 5: Station 4 PM_{2.5} and PM₁₀ concentration (24 hour average) – October 2022



6.1.5 Station 5 – Donald McLean Reserve

Table 12: Station 5 (Donald McLean Reserve AAQMS) PM2.5 and PM10 percentiles (24 hour average)

Parameter		Air quality objective ^B						
	Maximum	99 th	98 th	95 th	90 th	75 th	50th	(µg/m³)
PM _{2.5}	10	10	10	10	9.7	6.9	5.1	36
PM10	27	26	25	23	21	16	11	60

Note:

A Micrograms per cubic metre at 0°C and 101.3 kPa B SEPP(AQM) Intervention level Values rounded to two significant figures.



Figure 6: Station 5 PM_{2.5} and PM₁₀ concentration (24 hour average) – October 2022



6.1.6 Station 6 – Millers Road

Table 13: Station 6 (Millers Road AAQMS) PM2.5 and PM10 percentiles (24 hour average)

Parameter		Air quality objective ^B						
	Maximum	99 th	98 th	95 th	90 th	75 th	50th	(µg/m³)
PM _{2.5}	12	12	12	11	10	7.1	4.4	36
PM10	43	40	38	35	32	21	12	60

Note:

A Micrograms per cubic metre at 0°C and 101.3 kPa B SEPP(AQM) Intervention level Values rounded to two significant figures.



Figure 7: Station 6 PM_{2.5} and PM₁₀ concentration (24 hour average) – October 2022



6.1.7 Combined PM_{2.5} mass concentrations

Combined plots of the AAQMS PM_{2.5} and PM₁₀ are presented in Figure 8 and Figure 9 respectively.



Figure 8: Combined PM_{2.5} concentration (24 hour average) – October 2022



Figure 9: Combined PM₁₀ concentration (24 hour average) – October 2022

6.2 Nitrogen dioxide (NO₂)

 NO_2 (1 hour average) mass concentration statistics for the reporting period are given in Table 14. A plot of NO_2 (1 hour average) mass concentration for the reporting period is presented in Figure 10.

Parameter		SEPP (AQM) intervention level						
	Maximum	99 th	98 th	95 th	90 th	75 th	50th	(ppb)
NO ₂	60	40	33	29	25	19	13	140

Table 14: Station 4 (Primula Avenue AAQMS) NO2 percentiles (1 hour average)

Note:

A Parts per billion



Figure 10: Station 4 NO₂ concentration (1 hour average) – October 2022

6.3 **Carbon monoxide (CO)**

CO (1 hour average) mass concentration statistics for the reporting period are given in Table 15. A plot of CO (1 hour average) concentration for the reporting period is presented in Figure 11.

Parameter		SEPP (AQM) intervention leve	l						
	Maximum	99 th	98 th	95 th	90 th	75 th	50th	(ppm)	
СО	2.2	0.66	0.60	0.52	0.44	0.36	0.30	29	

Table 15: Station 4 (Primula Avenue AAQMS) CO percentiles (1 hour average)

Note:

Parts per million А



Figure 11: Station 4 CO concentration (1 hour average) – October 2022



6.4 Volatile organic compounds (BTEX)

VOC samples were collected from Station 4 (Primula Avenue), in an evacuated electro-polished and passivated stainless steel canister. Analysis involves separation by gas chromatography (GC) and measurement by mass selective (MS) detector

The procedure for sampling Volatile Organic Compounds (VOCs) using evacuated canisters, and for the subsequent analysis, is described in USEPA Method TO-15 "Determination of Volatile Organic Compounds (VOCs) in air collected in specially-prepared canisters and analysed by Gas Chromatography/Mass Spectrometry (GC/MS)".

Samples were analysed by Queensland Health (NATA Laboratory Accreditation No. 41) based on USEPA method TO-15 (Laboratory Report Nos. SSP81028, SSP81189, SSP81242).

The test method used was in accordance with Golder Source Test Method C9, "Canister (Evacuated) Sampling for VOC: In Ambient Air and Source Emissions".

BTEX (24 hour average) mass concentration statistics for the reporting period are given in Table 16. Laboratory certificates are presented in APPENDIX B.

Date	Sample no.	Benzene (ppb)	Toluene (ppb)	Ethylbenzene (ppb)	Total xylene isomers (ppb)
2/10/2022	22-2068	<0.5	0.8	<0.5	<1
8/10/2022	22-2069	<0.5	<0.5	<0.5	<1
14/10/2022	22-2114	<0.5	1.1	<0.5	<1
20/10/2022	22-2115	<0.5	<0.5	<0.5	<1
26/10/2022	22-2139	<0.5	<0.5	<0.5	<1
NEPM	1 MIL ^A	3.0 ^B	1000	NA	250

Table 16: Station 4 - Primula Avenue AAQMS BTEX concentrations (24 hour average)

Note:

A National Environment Protection Measure (Air Toxics) Monitoring Investigation Level

B Annual average

Sample analysis conducted by Queensland Health, NATA Accreditation No. 41/ Eurofins Pty Ltd, NATA Accreditation No. 1261. Analysis dates: 27/10/2022 (22-2068, 22-2069); 18/11/2022 (22-2114, 22-2115, 22-2139).



6.5 Meteorological parameters

6.5.1 Ambient temperature

Ambient Temperature data for all AAQMS sites are presented in Figure 12 for the reporting period.



Figure 12: Ambient temperature (1 hour average) All AAQMS - October 2022

6.5.2 Relative humidity

Relative Humidity data for all AAQMS sites are presented in Figure 13 for the reporting period.





Figure 13: Relative humidity (1 hour average) All AAQMs - October 2022

6.5.3 Atmospheric pressure

Atmospheric pressure data for Station 4 (Primula Avenue AAQMS) is presented in Figure 14 for the reporting period.



Figure 14: Atmospheric pressure (1 hour average) Station 4 Primula Avenue - October 2022

6.5.4 Wind speed

Wind Speed data for all AAQMS sites are presented in Figure 15 for the reporting period.



Figure 15: Wind speed (1 hour average) All AAQMs – October 2022

6.5.5 Wind rose – Station 1 (Yarraville Gardens)

A wind rose (1 hour average) for Yarraville Gardens AAQMS is presented in Figure 16.



Figure 16: Wind speed (1 hour average) Station 1 - Yarraville Gardens



6.5.6 Wind rose – Station 2 (Francis Street)

A wind rose (1 hour average) for Station 2 (Francis Street AAQMS) is presented in Figure 17.



Figure 17: Wind speed (1 hour average) Station 2 - Francis Street

6.5.7 Wind rose – Station 3 (Railway Reserve)

A wind rose (1 hour average) for Station 3 (Railway Reserve AAQMS) is presented in Figure 18.



Figure 18: Wind speed (1 hour average) Station 3 - Railway Reserve



6.5.8 Wind rose – Station 4 (Primula Avenue)

A wind rose (1 hour average) for Station 4 (Primula Avenue AAQMS) is presented in Figure 19.



Figure 19: Wind speed (1 hour average) Station 4 - Primula Avenue

6.5.9 Wind rose – Station 5 (Donald McLean Reserve)

A wind rose (1 hour average) for Station 5 (Donald McLean Reserve AAQMS) is presented in Figure 20.



Figure 20: Wind speed (1 hour average) Station 5 - Donald McLean Reserve

7.0 QUALITY ASSURANCE

7.1 Data capture

Data capture is defined as the number of valid data periods collected divided by the number of available data periods. Valid data excludes periods where the instrument is unavailable due to calibration and maintenance and excludes periods where the data has been rejected due to quality assurance/data validation procedures.

Automatic calibrations are conducted for NO_2 and CO daily to monitor and correct instrument drift where necessary. NO_2 and CO automatic calibrations are conducted once per day between 01:00 and 01:45 hours.

Data capture statistics for the reporting period 1 October to 31 October 2022 are shown in Table 17. Averages were only collected for those periods where the 5 minute data constituted 75% data capture. Data capture statistics for October 2022 were above 90 percent for all parameters at all stations.

Parameter	Averaging period	Station	Collected periods	Available periods	Data capture¹
PM _{2.5}	24 hour	1 – Yarraville Gardens	31	31	100%
	24 hour	2 – Francis Street	31	31	100%
	24 hour	3 – Railway Reserve	31	31	100%
	24 hour	4 – Primula Avenue	31	31	100%
	24 hour	5 – Donald McLean Reserve	31	31	100%
	24 hour	6 – Millers Road	31	31	100%
PM ₁₀	24 hour	1 – Yarraville Gardens	31	31	100%
	24 hour	2 – Francis Street	31	31	100%
	24 hour	3 – Railway Reserve	31	31	100%
	24 hour	4 – Primula Avenue	31	31	100%
	24 hour	5 – Donald McLean Reserve	31	31	100%
	24 hour	6 – Millers Road	31	31	100%
NO ₂	1 hour	4 – Primula Avenue	712	744	96%
СО	1 hour	4 – Primula Avenue	712	744	96%
Ambient temperature	1 hour	1 – Yarraville Gardens	744	744	100%
d relative numbery	1 hour	2 – Francis Street	742	744	100%
	1 hour	3 – Railway Reserve	739	744	99%
	1 hour	4 – Primula Avenue	744	744	100%
	1 hour	5 – Donald McLean Reserve	741	744	100%
	1 hour	6 – Millers Road	744	744	100%
Atmospheric pressure	1 hour	4 – Primula Avenue	744	744	100%

Table 17: Data Capture



Wind speed and	1 hour	1 – Yarraville Gardens	744	744	100%
	1 hour	2 – Francis Street	742	744	100%
	1 hour	3 – Railway Reserve	740	744	99%
	1 hour	4 – Primula Avenue	741	744	100%
	1 hour	5 – Donald McLean Reserve	742	744	100%

Note:

1 Rounded to two significant figures

7.2 Data validation

Data contained in this report has been validated against performance and calibration requirements for each instrument. Data during commissioning, maintenance and calibration periods has been removed from the validated data sets. APPENDIX A lists the data exceptions for all AAQMS. Missing data periods during automatic calibrations of the gaseous atmospheric contaminants NO₂ and CO are not shown.

8.0 **DISCUSSION**

Table 18 presents the maximum measured concentration during the reporting period at Station 1 for $PM_{2.5}$ and PM_{10} compared with the respective criteria.

Table 18: Station 1 Summary – October 2022

Parameter	Units	Averaging period	Maximum concentration	Air quality objective ^A	Exceedances ^B
PM _{2.5}	ug/m ³	24 hour	12	25	Nil
PM ₁₀	ug/m ³	24 hour	30	50	Nil

Notes:

A – SEPP(AAQ) objective

B - Exceedances refers to the number of individual days the criterion was exceeded at any station.

Table 19 presents the maximum measured concentration during the reporting period at Station 2, Station 3, Station 5 and Station 6 for $PM_{2.5}$ and PM_{10} compared with the respective criteria.

Parameter	Units Av	Averaging period	Maximum concentration				Air quality	Exceedences
			Station 2	Station 3	Station 5	Station 6	objective ^A	Exceedances
PM _{2.5}	ug/m ³	24 hour	12	11	10	12	36	Nil
PM ₁₀	ug/m ³	24 hour	29	22	27	43	60	Nil

Table 19: Station 2, Station 3, Station 5 and Station 6 Summary – October 2022

Notes:

A - SEPP(AQM) Intervention level

B - Exceedances refers to the number of individual days the criterion was exceeded at any station.

Table 20 presents maximum measured concentration during the reporting period at Station 4 for PM_{2.5}, PM₁₀, NO₂, CO and BTEX compared with the respective criteria.



Parameter	Units	Averaging period	Maximum concentration	Air quality objective	Exceedances ^c
PM _{2.5}	ug/m ³	24 hour	13	36 ^A	Nil
PM10	ug/m ³	24 hour	45	60 ^A	Nil
NO ₂	ppb	1 hour	60	140 ^A	Nil
СО	ppm	1 hour	2.2	29 ^A	Nil
Benzene	ppb	24 hour	<0.5	3.0 ^B	Nil
Toluene	ppb	24 hour	1.1	1000 ^B	Nil
Total xylene isomers	ppb	24 hour	<1	250 ^B	Nil

 Table 20: Station 4 Summary – October 2022

Notes:

A - SEPP(AQM) Intervention level

B - Air NEPM Monitoring investigation level

C - Exceedances refers to the number of individual days the criterion was exceeded at any station.

October 2022 ambient air quality monitoring programme results were less than the respective air quality objectives for all parameters measured at all ambient air quality stations.

Data capture statistics for October 2022 were above 90 percent for all parameters at all stations.

A construction area (Millers Road exit ramp and noise wall relocation) is now adjacent Station 4, as a result, the measured pollutant concentrations may not be representative of traffic emissions.

9.0 IMPORTANT INFORMATION RELATING TO THIS REPORT

Your attention is drawn to the document titled - "Important Information Relating to this Report", which is included in APPENDIX C of this report. The statements presented in that document are intended to inform a reader of the report about its proper use. There are important limitations as to who can use the report and how it can be used. It is important that a reader of the report understands and has realistic expectations about those matters. The Important Information document does not alter the obligations Golder Associates has under the contract between it and its client.



Signature Page

Golder Associates Pty Ltd

Autrye 7

Anthony Myszka Environmental Technician

AM/MDT/am

M.D. ful.

Mark Tulau Principal Environmental Scientist - Air and Noise

Golder and the G logo are trademarks of Golder Associates Corporation

j:\2017\1789878 - cpb contractors westgate tunnel aaqms\correspondence out\1789878-051_2022_oct\1789878-051-r-rev0_aaqms_2022_oct.docx





APPENDIX A

Data Exceptions

Date from	Date to	Station	Parameters	Reason
20/10/2022 12:45	20/10/2022 13:25	1	PM _{2.5} / PM ₁₀	Maintenance / calibration
26/10/2022 16:05	26/10/2022 19:05	1	PM _{2.5}	Invalid data ¹
28/10/2022 00:05	28/10/2022 05:00	1	PM _{2.5}	Invalid data ¹
20/10/2022 13:35	20/10/2022 13:55	2	PM _{2.5} / PM ₁₀	Maintenance / calibration
20/10/2022 11:10	20/10/2022 11:55	3	PM _{2.5} / PM ₁₀	Maintenance / calibration
20/10/2022 10:50	20/10/2022 12:00	3	Temperature / RH	Maintenance / calibration
11/10/2022 11:35	11/10/2022 14:05	3	Temperature / RH	Maintenance / calibration
11/10/2022 12:40	11/10/2022 14:30	3	Wind Sensor	Maintenance / calibration
20/10/2022 12:30	20/10/2022 13:00	3	Wind Sensor	Maintenance / calibration
21/10/2022 10:55	21/10/2022 11:45	4	CO, NO, NO ₂ , NO _x	Maintenance / calibration
21/10/2022 11:00	21/10/2022 11:30	4	PM _{2.5} / PM ₁₀	Maintenance / calibration
9/10/2022 12:00	9/10/2022 16:00	4	PM _{2.5}	Invalid data ¹
20/10/2022 08:50	20/10/2022 11:55	5	PM _{2.5}	Maintenance / calibration
3/10/2022 16:05	3/10/2022 19:00	5	PM _{2.5}	Invalid data ¹
6/10/2022 09:10	6/10/2022 14:45	5	PM _{2.5}	Invalid data ¹
20/10/2022 00:00	20/10/2022 02:55	5	PM ₁₀	Invalid data ¹
20/10/2022 09:25	20/10/2022 10:55	5	PM ₁₀	Maintenance / calibration
6/10/2022 09:10	6/10/2022 10:00	5	Wind Sensor	Maintenance / calibration
21/10/2022 10:05	21/10/2022 10:45	6	PM _{2.5} / PM ₁₀	Maintenance / calibration
27/10/2022 03:05	27/10/2022 06:50	6	PM _{2.5}	Invalid data ¹
27/10/2022 23:05	28/10/2022 05:45	6	PM _{2.5}	Invalid data ¹
25/10/2022 01:20	25/10/2022 06:40	6	PM ₁₀	Invalid data ¹
29/10/2022 18:35	29/10/2022 22:40	6	PM ₁₀	Invalid data ¹

Note: 1 - In the opinion of the data reviewer

APPENDIX B

Laboratory Certificates





Forensic and Scientific Services

CERTIFICATE OF ANALYSIS

CLIENT:

WSP Golder Associates Building 7, Botanicca Corporate Park 570 - 588 Swan Street Richmond VIC 3121

ATTN: Anthony Evans

Laboratory Reference Client Order Number Quote Number Client Project Client Batch Reference Date Received Date Commenced Laboratory Number/s : SSP81028

: n/a

: n/a

: n/a

: n/a

: 20-Oct-2022

: 27-Oct-2022

: 22KS4208-4209

CC: Anthony Myszka

Submitting Authority	: Golder Associates
Number of Samples	: Two (2) Summa canisters
Reason for Analysis	: Analysis of Volatile Organic Compounds (VOCs) in air
Method/s of Analysis	: QIS28237 – Identification, confirmation and quantitation of Volatile Organic Compounds (VOCs) by GCMS using an in-house method as per EPA method TO15
Remarks	: Sample details and results are summarised in Table 1.

David Pass Senior Chemist, Organics Laboratory 28th October 2022





SSP81028

This report overrides all previous reports. The results relate solely to the sample/s as received and are limited to the specific tests undertaken as listed on the report. The results of this report are confidential and are not to be used or disclosed to any other person or used for any other purpose, whether directly or indirectly, unless that use is disclosed or the purpose is expressly authorised in writing by Queensland Health and the named recipient on this report. To the fullest extent permitted by law, Queensland Health will not be liable for any loss or claim (including legal costs calculated on an indemnity basis) which arise because of (a) problems related to the merchantability, fitness or quality of the sample/s, or (b) any negligent or unlawful act or omissions by Queensland Health that is connected with any activities or services provided by Queensland Health under this agreement (including the timing and/or method under which the sample/s were taken, stored or transported).

Enquiries David Pass Phone (+61 7) 3096 2854 Email David.Pass@health.qld.gov.au 39 Kessels Road Coopers Plains QLD 4108 AUSTRALIA PO Box 594 Archerfield QLD 4108 AUSTRALIA
 Phone
 (+61 7) 3096 2990

 Fax
 (+61 7) 3096 2977

 Email
 FSS@health.qld.gov.au

Table 1:	Results	for Summa	canister	analysis
----------	---------	-----------	----------	----------

Client F	Reference	22-2068	22-2069* Silco Canister #1737 n/a ambient air		
Sample	Туре	Silco Canister #2394			
Samplir	ng Time / Date	n/a			
Sample	Description	ambient air			
Method	Volatile Organic Compounds (VOCs) by GCMS	Units	Reporting Limit	22KS4208	22KS4209
28237	Benzene	vdqq	0.5	< LOR	<1.0R
28237	Toluene	ppbv	0.5	0.8	< LOR
28237	Ethylbenzene	ppbv	0.5	< LOR	< LOR
28237	m- & p-Xylene	ppbv	0.5	< LOR	< LOR
28237	o-Xylene	ppbv	0.5	< LOR	< LOR

*Sample submission form states 22-1069, value taken from canister tag Temperature and atmospheric pressure at time of sampling unavailable

This report overrides all previous reports. The results relate solely to the sample/s as received and are limited to the specific tests undertaken as listed on the report. The results of this report are confidential and are not to be used or disclosed to any other person or used for any other purpose, whether directly or indirectly, unless that use is disclosed or the purpose is expressly authorised in writing by Queensland Health and the named recipient on this report. To the fullest extent permitted by law, Queensland Health will not be liable for any loss or claim (including legal costs calculated on an indemnity basis) which arise because of (a) problems related to the merchantability, fitness or quality of the sample/s, or (b) any negligent or unlawful act or omissions by Queensland Health that is connected with any activities or services provided by Queensland Health under this agreement (including the timing and/or method under which the sample/s were taken, stored or transported).



Forensic and Scientific Services

CERTIFICATE OF ANALYSIS

CLIENT:

WSP Golder Associates Building 7, Botanicca Corporate Park 570 - 588 Swan Street Richmond VIC 3121

ATTN: Anthony Evans

Laboratory Reference **Client Order Number** Quote Number **Client Project** Client Batch Reference Date Received Date Commenced Laboratory Number/s

: SSP81189 : n/a : n/a : n/a : n/a : 2-Nov-2022 : 18-Nov-2022 : 22KS4412-4413

CC: Anthony Myszka

Submitting Authority	: Golder Associates
Number of Samples	: Two (2) Summa canisters
Reason for Analysis	: Analysis of Volatile Organic Compounds (VOCs) in air
Method/s of Analysis	: QIS28237 – Identification, confirmation and quantitation of Volatile Organic Compounds (VOCs) by GCMS using an in-house method as per EPA method TO15
Remarks	: Sample details and results are summarised in Table 1.

David Pass Senior Chemist, Organics Laboratory 21st November 2022



SSP81189

This report overrides all previous reports. The results relate solely to the sample/s as received and are limited to the specific tests undertaken as listed on the report. The results of this report are confidential and are not to be used or disclosed to any other person or used for any other purpose, whether directly or indirectly, unless that use is disclosed or the purpose is expressly authorised in writing by Queensland Health and the named recipient on this report. To the fullest extent permitted by law, Queensland Health will not be liable for any loss or claim (including legal costs calculated on an indemnity basis) which arise because of (a) problems related to the merchantability, fitness or quality of the sample/s, or (b) any negligent or unlawful act or omissions by Queensland Health that is includent by increasing entertable in the report. connected with any activities or services provided by Queensland Health under this agreement (including the timing and/or method under which the sample/s were taken, stored or transported). Phone

Enquiries David Pass Phone (+61 7) 3096 2854 Email David.Pass@health.qld.gov.au

39 Kessels Road Coopers Plains QLD 4108 AUSTRALIA

PO Box 594 Archerfield QLD 4108 AUSTRALIA

Fax

(+61 7) 3096 2990 (+61 7) 3096 2977 FSS@health.qld.gov.au Email

CERTIFICATE OF ANALYSIS

Laboratory Reference: SSP81189 Laboratory Number: 22KS4412-4413

Client F	Reference	22-2114	22-2115 Silco Canister #1745		
Sample	Туре	Silco Canister #1730			
Sampling Time / Date					n/a
Sample Description					ambient air
Method	Volatile Organic Compounds (VOCs) by GCMS	Units	Reporting Limit	22KS4412	22KS4413
28237	Benzene	vdqq	0.5	< LOR	< LOR
28237	Toluene	ppbv	0.5	1.1	< LOR
28237	Ethylbenzene	ppbv	0.5	< LOR	< LOR
28237	m- & p-Xylene	ppbv	0.5	< LOR	< LOR
28237	o-Xvlene	nnhy	0.5	< LOR	<10R

Table 1: Results for Summa canister analysis

Temperature and atmospheric pressure at time of sampling unavailable

This report overrides all previous reports. The results relate solely to the sample/s as received and are limited to the specific tests undertaken as listed on the report. The results of this report are confidential and are not to be used or disclosed to any other person or used for any other purpose, whether directly or indirectly, unless that use is disclosed or the purpose is expressly authorised in writing by Queensland Health and the named recipient on this report. To the fullest extent permitted by law, Queensland Health will not be liable for any loss or claim (including legal costs calculated on an indemnity basis) which arise because of (a) problems related to the merchantability, fitness or quality of the sample/s, or (b) any negligent or unlawful act or omissions by Queensland Health that is connected with any activities or services provided by Queensland Health under this agreement (including the timing and/or method under which the sample/s were taken, stored or transported).



Forensic and Scientific Services

: SSP81242

: 8-Nov-2022

: 18-Nov-2022

: 22KS4446-4447

: n/a

: n/a

: n/a

: n/a

Laboratory Reference

Client Order Number

Client Batch Reference

Quote Number

Date Received

Date Commenced

Laboratory Number/s

Client Project

CERTIFICATE OF ANALYSIS

CLIENT:

WSP Golder Associates Building 7, Botanicca Corporate Park 570 - 588 Swan Street Richmond VIC 3121

ATTN: Anthony Evans

CC: Anthony Myszka

- Submitting Authority : Golder Associates
- Number of Samples : Two (2) Summa canisters

Reason for Analysis : Analysis of Volatile Organic Compounds (VOCs) in air

Method/s of Analysis : QIS28237 – Identification, confirmation and quantitation of Volatile Organic Compounds (VOCs) by GCMS using an in-house method as per EPA method TO15

Remarks

: Sample details and results are summarised in Table 1.

David Pass Senior Chemist, Organics Laboratory 21st November 2022



NATA Accredited Laboratory 41 Accredited for compliance with ISO/IEC 17025 -Testing

SSP81242

This report overrides all previous reports. The results relate solely to the sample/s as received and are limited to the specific tests undertaken as listed on the report. The results of this report are confidential and are not to be used or disclosed to any other person or used for any other purpose, whether directly or indirectly, unless that use is disclosed or the purpose is expressly authorised in writing by Queensland Health and the named recipient on this report. To the fullest extent permitted by law, Queensland Health will not be liable for any loss or claim (including legal costs calculated on an indemnity basis) which arise because of (a) problems related to the merchantability, fitness or quality of the sample/s, or (b) any negligent or unlawful act or omissions by Queensland Health under this agreement (including the timing and/or method under which the sample/s were taken, sfored or transported).

Enquiries David Pass

Phone (+61 7) 3096 2854 Email David.Pass@health.qld.gov.au 39 Kessels Road Coopers Plains QLD 4108 AUSTRALIA PO Box 594 Archerfield QLD 4108 AUSTRALIA Phone (+61 7) 3096 2990 Fax (+61 7) 3096 2977 Email FSS@health.qld.gov.au

Client F	leference	22-2139	22-2140 Silco Canister #5403 n/a ambient air		
Sample	Туре	Silco Canister #1744			
Samplir	ng Time / Date	n/a			
Sample	Description	ambient air			
Method	Volatile Organic Compounds (VOCs) by GCMS	Units	Reporting Limit	22KS4446	22KS4447
28237	Benzene	vdqq	0.5	< LOR	< LOR
28237	Toluene	ppbv	0.5	< LOR	< LOR
28237	Ethylbenzene	ppbv	0.5	< LOR	< LOR
28237	m- & p-Xylene	ppbv	0.5	< LOR	< LOR
28237	o-Xylene	vdqq	0.5	< LOR	< LOR

Table 1: Results for Summa canister analysis

Temperature and atmospheric pressure at time of sampling unavailable

This report overrides all previous reports. The results relate solely to the sample/s as received and are limited to the specific tests undertaken as listed on the report. The results of this report are confidential and are not to be used or disclosed to any other person or used for any other purpose, whether directly or indirectly, unless that use is disclosed or the purpose is expressly authorised in writing by Queensland Health and the named recipient on this report. To the fullest extent permitted by law, Queensland Health will not be liable for any loss or claim (including legal costs calculated on an indemnity basis) which arise because of (a) problems related to the merchantability, fitness or quality of the sample/s, or (b) any negligent or unlawful act or omissions by Queensland Health that is connected with any activities or services provided by Queensland Health under this agreement (including the timing and/or method under which the sample/s were taken, stored or transported).

APPENDIX C

Important Information Relating to this Report





The document ("Report") to which this page is attached and of which this page forms a part has been issued by Golder Associates Pty Ltd ("Golder") subject to the important limitations and other qualifications set out below.

This Report constitutes or is part of services ("Services") provided by Golder to its client ("Client") under and subject to a contract between Golder and its Client ("Contract"). The contents of this page are not intended to and do not alter Golder's obligations (including any limits on those obligations) to its Client under the Contract.

This Report is provided for use solely by Golder's Client and persons acting on the Client's behalf, such as its professional advisers. Golder is responsible only to its Client for this Report. Golder has no responsibility to any other person who relies or makes decisions based upon this Report or who makes any other use of this Report. Golder accepts no responsibility for any loss or damage suffered by any person other than its Client as a result of any reliance upon any part of this Report, decisions made based upon this Report or any other use of it.

This Report has been prepared in the context of the circumstances and purposes referred to in, or derived from, the Contract and Golder accepts no responsibility for use of the Report, in whole or in part, in any other context or circumstance or for any other purpose.

The scope of Golder's Services and the period of time they relate to are determined by the Contract and are subject to restrictions and limitations set out in the Contract. If a service or other work is not expressly referred to in this Report, do not assume that it has been provided or performed. If a matter is not addressed in this Report, do not assume that any determination has been made by Golder in regards to it.

At any location relevant to the Services conditions may exist which were not detected by Golder, in particular due to the specific scope of the investigation Golder has been engaged to undertake. Conditions can only be verified at the exact location of any tests undertaken. Variations in conditions may occur between tested locations and there may be conditions which have not been revealed by the investigation and which have not therefore been taken into account in this Report.

Golder accepts no responsibility for and makes no representation as to the accuracy or completeness of the information provided to it by or on behalf of the Client or sourced from any third party. Golder has assumed that such information is correct unless otherwise stated and no responsibility is accepted by Golder for incomplete or inaccurate data supplied by its Client or any other person for whom Golder is not responsible. Golder has not taken account of matters that may have existed when the Report was prepared but which were only later disclosed to Golder.

Having regard to the matters referred to in the previous paragraphs on this page in particular, carrying out the Services has allowed Golder to form no more than an opinion as to the actual conditions at any relevant location. That opinion is necessarily constrained by the extent of the information collected by Golder or otherwise made available to Golder. Further, the passage of time may affect the accuracy, applicability or usefulness of the opinions, assessments or other information in this Report. This Report is based upon the information and other circumstances that existed and were known to Golder when the Services were performed and this Report was prepared. Golder has not considered the effect of any possible future developments including physical changes to any relevant location or changes to any laws or regulations relevant to such location.

Where permitted by the Contract, Golder may have retained subconsultants affiliated with Golder to provide some or all of the Services. However, it is Golder which remains solely responsible for the Services and there is no legal recourse against any of Golder's affiliated companies or the employees, officers or directors of any of them.

By date, or revision, the Report supersedes any prior report or other document issued by Golder dealing with any matter that is addressed in the Report.

Any uncertainty as to the extent to which this Report can be used or relied upon in any respect should be referred to Golder for clarification.



golder.com